

## 8000T All-Temp



Available  
from stock  
on ZipShip

<b>Media Type</b>	Label	✓	<b>Adhesive Type</b>	Permanent	✓
	Receipt			Removable	
	Tag			No Adhesive	
	Wristband		<b>Environment</b>	Indoor	✓
<b>Material Type</b>	Paper	✓		Outdoor	
	Synthetic		<b>Properties</b>	Cold Temperature	✓
<b>Printing Technology</b>	Direct Thermal (no Ribbon Required)			Deep Freeze	✓
	Thermal Transfer (Ribbon Required)	✓		High Temperature	
<b>Finish</b>	Matte	✓		Ultra High Temperature	
	Gloss			High Tack	
				Chemical Resistance	-

### Additional Features

- Special adhesive is resistant to a wide temperature range, both at application and throughout the life of the label
- Produces excellent quality images especially rotated barcodes, graphics and small character even at higher print speeds
- Adhesive offers strength and excellent adhesion to a wide variety of surfaces
- BPA free
- Latex free adhesive

### Suggested Applications

- Labelling of packaging material
- Compliance labelling
- Work in progress; especially in applications of varying temperatures
- Product identification
- Warehouse labelling especially where long-term storage and varying temperatures apply
- Cold storage labelling

### Technical Specifications

	Description	Caliper
<b>Facestock</b>	Ultra smooth white topcoated paper	74 microns
<b>Adhesive</b>	Permanent acrylic adhesive	18 microns
<b>Liner</b>	Semi-bleached kraft liner	64 microns
	<b>Total</b>	<b>156 microns ±10%</b>

<b>Recommended Zebra Printers:</b>	P4T™, desktop, mid-range and high-performance printers
<b>Recommended Zebra Ribbons:</b>	2300, 2100, 3400, 3200
<b>Minimum Application Temperature:</b> When the label is applied, the environment and surface should be above this temperature	-29°C
<b>Service Temperature Range:</b> Following correct application and appropriate dwell time (usually 24hrs) the media will withstand this temperature range	-54°C to 93°C
<b>Recommended Storage Conditions:</b> Storage of product before use	1 year duration when stored at 22°C at 50% RH
<b>Expected Life Span in Application:</b> Following correct application and appropriate dwell time (usually 24hrs) we expect, but do not warrant, a life span as indicated	Indoor use, 1 year+

### **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

For testing of this material, please order sample roll SAMPLE5024.