

SEE MORE. DO MORE.

Z-Select 2000D Removable

Removable Labels

Direct Thermal

Description

A smooth, bright white, direct thermal label stock which produces high contrast black images with Zebra thermal transfer printers. The thermally sensitive top coating ensures maximum printhead life, gives superior smudge resistance and protects the label from environmental conditions. The rubber based removable adhesive provides good initial tack to a wide range of packaging, films and papers and good removability after application.

Note: Z-Select 2000D Removable is not recommended for applications involving direct and long term exposure to sunlight or extreme heat.

Suggested Applications

- Retail applications requiring clean removability e.g. labelling of gifts, books and CDs
- Shelf edge labelling
- Product identification
- Removable tote bin, pallet or shelf edge labels in warehousing applications

Technical Specifications

	Description	Caliper	
Facestock	84 gsm white coated thermal imaging paper		80 microns
Adhesive	Rubber based removable adhesive		16 microns
Liner	62gsm Glassine liner		56 microns
		Total	152 microns

Recommended Zebra printers: Mobile, desktop, mid-range and high-performance thermal printers

Minimum application temperature: -5°C

Recommended ribbon: n/a

Service temperature range: -40°C to 50°C

Recommended storage conditions: One-year duration when stored at 0°C to 21°C at 35% to 50% RH

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application. For testing of this material, please order the sample roll SAMPLE5648.

